



NEO GHN-F

BOMBAS DE ALTA EFICIENCIA ENERGETICA PARA CALEFACCIÓN Y CLIMATIZACIÓN (Según normativa EUP/ERP) HIGH ENERGY-EFFICIENT CIRCULATOR PUMP (According to EUP/ERP regulation)

Aplicaciones

Bomba electrónica de bajo consumo, indicada para circulación de agua en sistemas de calefacción y climatización.

Materiales

Cuerpo de bomba hierro fundido
Eje del impulsor plástico
Eje cerámico
Placa de soporte: acero inoxidable
Soporte cerámico

Motor

Compatibilidad electromagnética
EL641/2009-EE 1 < 0.23
Botón on/off
Bajo consumo energético
Ajuste automático a las condiciones ambientales
Protección tipo IP44
Tipo de aislamiento F
Nivel de sonoridad < 45 db

Limitaciones

Temperatura liquido -10°C a 95°C
Temp. ambiente 0 a 40°C
Presión max. De trabajo 10 bar
Rango de flujo 34 m3/h
Contrabridas incluidas

Applications

This low consumption electronic pump is indicated for the circulation of water in Heating and climatization systems.

Materials

Cast iron pump body
Plastic impeller shaft
Ceramic shaft
Supportplate: stainless Steel
Ceramic Support

Motor

Electromagnetic compatibility
EL641/2009-EE < 0.23
On/off Button
Low power consumption
Automatic ajustment to ambient conditions
Protection type IP44
Insulation type F
Loudness < 45 db

Limitations

Liquid temperature -10°C a 95°C
Ambient temperture 0 a 40°C
Max. Working pressure 10 bar
Flow range 34 m3/h
Counter flanges included



MODELO	Tensión (V)	P. max (w)	Q max (l/h)	mca	Distancia bridas	DN	Codigo EAN	Peso (Kg)
NEOGHN 32/120-F	220	329	9.500	12	220	32	8436028587254	17
NEOGHN 40/120-F		450	15.000	12	250	40	8436028587261	17
NEOGHN 40/180-F		600	17.000	16	250	40	8436028587278	17
NEOGHN 50/120-F		551	23.000	12	280	50	8436028587285	19
NEOGHN 50/180-F		800	26.000	16	280	50	8436028587292	19
NEOGHN 65/120-F		780	34.000	12	340	65	8436028587308	23

